

4VIPVT8-R / R-MM SERIES

Application

T8 LED louver fitting (RECESSED T-BAR CEILING) is designed to use for offices, libraries, convenience stores, discount stores, classroom etc.

Specification

Input Voltage	200-240 V AC
Power Factor	0.9
IP Rating	IP20
Rendering Index	> 80
LED Operating Temperature	0 to 35 Degree Celsius
LED Operating Life	50, 000 Hrs
CCT (K)	3000K, 4000K, 6500K
Dimmable	Non Dimmable
Mounting Method	Recessed T-Bar Ceiling Mounted
Housing	Mild Steel Fitting Electrostatically Polyester Powder Coated
Fitting Thickness	0.5mm

Ordering Data



Part No.	No. of T8 LED Tube	Dimension (mm)
EVO-VIPVT8-R-2424	2	1213 (L) X 604 (W)
EVO-VIPVT8-R-3424	3	1213 (L) X 604 (W)
EVO-VIPVT8-R-MM-2424	2	1195 (L) X 595 (W)
EVO-VIPVT8-R-MM-3424	3	1195 (L) X 595 (W)

Remark: R= Imperial, R-MM= Metric.

Related Product : Applicable with digital catalogue only
(Please click the product photo to redirect towards the respective cut-sheet)



* Product specification subject to change according to technology improvement.